

AMENDMENTS TO THE CLAIMS

1. (currently amended) A passive hardware system, ~~adjustable vertically as comprising at~~
least panels, at least one said panel having an upstream and a downstream side, said
5 system installed ~~in a waterway~~ upstream from ~~at least one a~~ barrier to the downstream
migration of ~~said~~ fish in ~~said a~~ waterway, said barrier having at least an upstream and a
downstream side,
wherein said system ~~installed and maintained to attract and collect fish in to a collector~~
gallery by passively simulating at least one natural hydraulic cue to which fish are
10 responsive, and
wherein ~~by adjusting~~ said system adjusts to ~~existing~~ changing hydraulic conditions of
said waterway, and
wherein said panels of said system are movable vertically without changing the
horizontal orientation of said system; and
15 wherein said fish ~~that are thus~~ attracted ~~by said system~~ circumvent said at least one
barrier.

2. (currently amended) The system of claim 1 in which said ~~system~~ passive simulation
~~provides at least one natural hydraulic cue that~~ elicits an instinctive response of said fish
20 to select a portion of said waterway enclosed at least in part by said system and having a
near maximum downstream velocity vector, u , and at least minimum strain rate variables
in the downstream direction with respect to the depth and the width of said waterway,
wherein said variables are represented mathematically as $\frac{\partial u}{\partial z}$ and $\frac{\partial u}{\partial y}$, respectively, and
wherein both said variables ideally approach zero.

3. (original) The system of claim 2 comprising at least an oven hood surface bypass
collector (OH-SBC), having length, width and depth, a top and a bottom, an interior
surface and an exterior surface, a main portion with at least one slot opening at said

bottom and at least one extension that projects upstream from said at least one barrier along said width,

wherein said extension eliminates at least one zone of dead water that may be adjacent said upstream side of said barrier, and

5 wherein said OH-SBC is positioned with said length adjacent and parallel to said upstream side of said at least one barrier, and

wherein said top is generally parallel to the surface of said water in which said OH-SBC operates, and

wherein said depth is selected to permit passage of fish of a pre-specified size.

10 4. (previously amended) The system of claim 3, the OH-SBC further comprising:

at least one internal sluiceway circumscribed at least in part by said extension,

wherein said extension is wedge shaped with the point of the wedge positioned farthest away upstream from said main portion,

15 wherein said extension maintains the same profile on its top as said main portion, being an unbroken extension thereof, and

wherein said at least one internal sluiceway runs parallel to said upstream side of said at least one barrier;

at least one collector gallery that parallels said sluiceway immediately adjacent

20 said upstream side of said at least one barrier and is circumscribed at least in part

by said main portion of said OH-SBC,

wherein said fish are attracted to said collector gallery by said simulated hydraulic cue maintained by said system, and

wherein said fish are moved around said barrier by at least partially de-watering said

collector gallery; and

at least one articulating extension affixed to said lower part of said collector gallery,

wherein said articulating extension at least partially controls the angle of attack of the water that flows under said collector gallery.

5 5. (original) The system of claim 3 further comprising at least one sensor, wherein said at least one sensor alerts to changing hydraulic conditions, permitting adjustment of said system.

10 6. (original) The system of claim 3 further comprising adjustable connections for affixing said OH-SBC to at least one portion of said upstream side of said barrier.

15 7. (currently amended) The system of claim 1 in which said at least one barrier is selected from the group consisting of a dam, a hydroelectric powerhouse, a weir, a boom, a berm, a sluice gate, and a spillway, and combinations thereof, wherein each member of said group has at least one intake on said upstream side.

20 8. (original) The system of claim 3 in which said OH-SBC comprises multiple modules.

9. (previously amended) The system of claim 8 in which said modules are associated with at least one de-watering screen for controlling the water velocity in each of said multiple modules.

25 10. (previously amended) The system of claim 8 in which said multiple modules are connected by a manifold such that the water from each of said multiple modules is maintained in a chamber associated with each of said multiple modules.

11. (previously amended) The system of claim 7 in which said system is movable vertically without changing the horizontal orientation of said system to facilitate operation at an optimum level with respect to said at least one intake, wherein said system operates to overcome at least one natural cue resultant from the operation of said at least one intake.

12. (currently amended): The system of claim 4 in which ~~at least one of said system natural hydraulic cues is implemented so as to at least partially impede~~ at least one visual cue, ~~that is precluded from occurring thus facilitating passage of said fish around said barrier.~~

13. (currently amended): The system of claim 12 in which said ~~at least one~~ visual cue is ~~precluded~~ impeded by painting the inside of said collector gallery a neutral color.

14. (previously amended) The system of claim 4 in which turbulence in said collector gallery is minimized by providing a smooth surface on said interior surface of said OH-SBC and applying a coating to said smooth surface, wherein said coating has a low coefficient of friction.

15. (currently amended) The system of claim 4 in which said wedge-shaped extension completely covers the space above and immediately upstream of ~~each of said at least one~~ an intakes of said a dam, wherein said wedge-shaped extension further displaces any eddy otherwise occurring above ~~each of said at least one intakes~~ and in the vicinity of said slot opening to said collector gallery.

16. (previously amended) The system of claim 4 further comprising at least one active stimulus provided in the region of said collector gallery, said stimulus selected from the group consisting essentially of natural light, artificial light, sound, and combinations thereof.

17. (currently amended) A passive method for facilitating the migration of fish downstream around a barrier in a waterway, said barrier having an upstream and a downstream side, comprising ~~employing establishing via a hardware system~~ passive means to simulate at least one natural hydraulic cue used by said fish, said passive means employed in a system establishing a partially enclosed path in the waterway near said upstream side of said barrier,
wherein said fish are attracted to said path established by the said passive simulation of at least one natural hydraulic cue that attracts said fish and that results in a change in at least one horizontal eddy that naturally occurs on said upstream side absent the presence of said system, and
wherein said path leads to a safe route around said barrier.

18. (previously amended) The method of claim 17 in which said at least one simulated hydraulic cue capitalizes on an instinctive response of said fish to select said partially enclosed path, said path having a near maximum downstream velocity vector, u , and said partially enclosed path at least minimizing strain rate variables in the downstream direction with respect to the depth and the width of said waterway,
wherein said variables are represented mathematically as $\frac{\partial u}{\partial z}$ and $\frac{\partial u}{\partial y}$, respectively, and
wherein both said variables ideally approach zero.

19. (previously amended) The method of claim 18 in which at least one additional strain rate variable is minimized,
wherein said at least one strain rate variables is selected from the group consisting of
 $\frac{\partial u}{\partial x}, \frac{\partial v}{\partial x}, \frac{\partial v}{\partial y}, \frac{\partial v}{\partial z}, \frac{\partial w}{\partial x}, \frac{\partial w}{\partial y}$ and $\frac{\partial w}{\partial z}$.

20. (previously amended) The method of claim 18 further comprising:

providing at least one Oven Hood Surface Bypass Collector (OH-SBC) having a length, width, depth, top, bottom, an interior and exterior side, upstream from and adjacent to said barrier, said length oriented parallel to said upstream side of said barrier and said top generally parallel to the surface of said water,

5 wherein said OH-SBC comprises:

a main portion with at least one slot opening at said bottom; and
at least one extension that projects upstream from said at least one barrier along said width,

10 at least one internal sluiceway circumscribed at least in part by said extension and running parallel to said upstream side of said at least one barrier;

at least one collector gallery that parallels said sluiceway immediately adjacent said upstream side of said at least one barrier and is

circumscribed at least in part by said main portion of said OH-SBC; and

15 at least one articulating extension affixed to said lower part of said collector gallery; and

at least partially de-watering said collector gallery to move said fish around said barrier.

20 21. (currently amended) A barrier to the downstream migration of fish, said barrier having at least an upstream and a downstream side and incorporating a ~~hardware~~ passive system adjustable vertically as installed in a waterway on said upstream side of said barrier, wherein said system is installed and maintained to attract and collect fish in a collector gallery by passively simulating at least one natural hydraulic cue to which fish are
25 attracted, and
wherein ~~by adjusting~~ said system is adjusted to existing hydraulic conditions of said waterway, and
wherein said fish that are attracted to said system circumvent said barrier.

22. (original) The barrier of claim 21 in which said barrier is selected from the group consisting of a dam, a hydroelectric powerhouse, a weir, a boom, a sluice gate, a spillway, a berm, and combinations thereof.

5
23. (previously presented): A system simulating at least one natural hydraulic cue to which fish are responsive in water, said at least one natural hydraulic cue eliciting an instinctive response of fish to select a portion of a stream having a near maximum downstream velocity vector, u , and at least minimum strain rate variables in the downstream direction
10 with respect to the depth and the width of the stream, said variables represented mathematically as $\frac{\partial u}{\partial z}$ and $\frac{\partial u}{\partial y}$, respectively, such that both said variables ideally approach zero, said system comprising at least an oven hood surface bypass collector (OH-SBC), having length, width and depth, a top and a bottom, an interior surface and an exterior surface, a main portion with at least one slot opening at said bottom and at least
15 one extension that projects upstream from at least one barrier along said width, said barrier having at least an upstream and a downstream side, said OH-SBC further comprising:

at least one internal sluiceway circumscribed at least in part by said extension,
said sluiceway running parallel to said upstream side of said at least one barrier,
20 wherein said OH-SBC is positioned with said length adjacent and parallel to said upstream side of said at least one barrier, and
wherein said top of said OH-SBC is generally parallel to the surface of said water in which said OH-SBC operates, and
wherein said extension eliminates at least one zone of dead water that may be adjacent
25 said upstream side of said barrier, and
wherein said extension is wedge shaped with the point of the wedge positioned farthest away from said main portion, and
wherein said extension maintains the same profile on its top as said main portion, being

an unbroken extension thereof;

at least one collector gallery that parallels said sluiceway and is circumscribed at least in part by said main portion of said OH-SBC,

at least one articulating extension affixed to said lower part of said collector gallery,

wherein said articulating extension at least partially controls the angle of attack of the water that flows under said collector gallery, and

wherein said fish are attracted to said collector gallery by said simulated hydraulic cue maintained by said system, and

wherein said fish that respond to said at least one simulated hydraulic cue circumvent at least one barrier to the downstream migration of said fish, and

wherein said fish are moved around said barrier by at least partially de-watering said collector gallery; and

wherein said depth is selected to permit passage of fish of a pre-specified size.

24. (previously presented): The system of claim 23 further comprising at least one sensor, wherein said at least one sensor alerts to changing hydraulic conditions, permitting adjustment of said system.

25. (currently amended): The system of claim 23 in which ~~at least one of said system is implemented so as to natural hydraulic cues is~~ at least partially impede at least one visual cue, ~~that is precluded from occurring thus facilitating passage of said fish around said barrier.~~

26. (currently amended): The system of claim 25 in which said at least one visual cue is ~~precluded~~ impeded by painting the inside of said collector gallery a neutral color.

27. (previously presented): The system of claim 23 in which turbulence in said collector gallery is minimized by providing a smooth surface on said interior surface of said OH-

SBC and applying a coating to said smooth surface, said coating having a low coefficient of friction.

28. (currently amended): The system of claim 23 in which at least one ~~additional~~ stimulus is provided in the region of said collector gallery, said stimulus selected from the group consisting essentially of natural light, artificial light, sound, and combinations thereof.

10

15

20

25